

Job: _____
Location: _____
Schedule No.: _____
System Designation: _____

Engineer: _____
Architect: _____
Date: _____
For: **Reference** **Approval** **Review** **Construction**

FEATURES

- DC Inverter Compressor Technology
- DC Condensing unit Motor
- Automatic start
- Compact Design
- Wired Control Included
- Washable filter

CTGP60168A-S

SPECIFICATION

Internal Unit

PERFORMANCE

	Turbo	1,354	CFM
Air Flow	High	1,295	
	Medium	1,118	
	Low	942	
External Static Pressure	Rated	N/A	Pa
	Range	N/A	Pa
Sound Pressure Level	Turbo	54	Pa
	High	53	
	Medium	49	
	Low	45	

ELECTRICAL DATA


Voltage	220-240/1/50-60	(V/Ph/Hz)
Current FLA	0.85	Amp
Power Input	250	Watts

DIMENSIONS

Net Dimensions	9.3x61.8x26.2	inch
	236x1570x665	mm
Weight	96.2	Lbs
	43.6	Kg
	108.0	Lbs
	49.0	Kg
Connection Pipe	3/8"	inch
	5/8"	inch
Connection Pipe distance	246.0	mts
	50.0	Feet
	98.4	mts
	30.0	Feet



CTGP60168A-S



	mm	inch
A	1570	61.8
B	235	9.3
C	1512	59.5
D	318	12.5
H	665	26.2

OPTIONAL ACCESSORIES

Wireless Thermostat (included)

Note – Due to Comfort Time ongoing commitment to quality, specifications, ratings and dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service, Maintenance and operation may cause property damage or personal injury. Installation, service and operation must be performed by a qualified installer, servicing and operation agency.

Job:

Engineer:

Location:

Architect:

Schedule No.:

Date:

System Designation:

 For: Reference Approval Review Construction

FEATURES

- DC Inverter Compressor Technology
- DC Condensing unit Motor
- Automatic start
- Compact Design
- Wired Control Included
- Washable filter
- Water Pump Included
- 9 level static pressure mode

SPECIFICATION

External Unit

PERFORMANCE

Nominal Cooling Capacity		53,200	Btu/h
	EER	2.89	W/W
	SEER	16	(Btu/h)/W
Nominal Heating Capacity		580,000	Btu/h
	HSPF	9	

Air Flow	3,472	CFM
----------	-------	-----

Operation Range	Cooling	5°F - 118°F	°F
		-15°C - 48°C	°C
	Heating	5°F - 75°F	°F
		-15°C - 24°C	°C

ELECTRICAL DATA

Voltage	220-240/1/50-60	(V/Ph/Hz)
Motor FLA	1.38	Amps
Compressor (RLA)	19.7	Amps
# Compressor	1	

GENERAL DATA

% Connection	100	%
Maximun Internal Units	1	
Sound Pressure Level	60	dBA
Refrigerant	R410A	
Factory Refrigerant Charge	8.38	Lbs
	134.04	Oz


DIMMENSIONS

Net Dimmensions	32.3 x 37 x 18.1	inch
	820 x 940 x 460	mm
Weight	211.7	Lbs
	96.0	Kg
	238.1	Lbs
	108.0	Kg



CTG060168A-S

DIMENSIONAL DRAWINGS - INCHES (MM)



CTG060168A-S		
Dimmension	mm	inch
A	940	37.0
B	530	20.9
C	820	32.3
D	610	24.0
E	486	19.1
G	460	18.1

OPTIONAL ACCESSORIES

Wireless Thermostat (included)

Note – Due to Comfort Time ongoing commitment to quality, specifications, ratings and dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service, Maintenance and operation may cause properly damage on personal injury. Installation, service and operation must be performed by a qualified installer, servicing and operation agency.