

Job: _____

Engineer: _____

Location: _____

Architect: _____

Schedule No.: _____

Date: _____

System Designation: _____

For: **Reference** **Approval** **Review** **Construction**

FEATURES

- All DC Inverter Technology
- Wide Application Range
- Flexible Control and Easy Maintenance
- 7 Speed
- Single Fan Motor
- Heating and Cooling
- High-lift Drain Pump
- Two Blowers
- Convenient Installation

PERFORMANCE

Nominal Cooling Capacity	Btu/h	47,770
	Kw	14
Nominal Heating Capacity	Btu/h	40,946
	Kw	12

ELECTRICAL DATA

Power Supply	V/Ph/Hz	220-240/1/50-60
Power Input (10 Pa) Cooling	Kw	480
Power Input (10 Pa) Heating	Kw	480
Min. Voltage	Volts	198
Max. Voltage	Volts	264
MCA	Amp	3.50
MFA	Amp	15
Rated Motor Output	Kw	0.34
FLA	Amp	2.80

GENERAL DATA

Airflow rate 3	m3/h (CFM)	2000 (1177)
	m3/h (CFM)	1917 (1128)
	m3/h (CFM)	1833 (1079)
	m3/h (CFM)	1750 (1030)
	m3/h (CFM)	1667 (981)
	m3/h (CFM)	1583 (932)
	m3/h (CFM)	1500 (883)
External static pressure 4	Pa	150 (100~250)
Sound pressure level 5	dB(A)	48
	dB(A)	47
	dB(A)	46
	dB(A)	45
	dB(A)	44
	dB(A)	43
	dB(A)	42
Dimmension	Net (mm)	1322x493x691
	Packed (mm)	1436x450x768
Weight Net/Gross	KG	68/76
	(Lbs)	149.9/167.6
Refrigerant type		R410A
Design pressure (H/L)	Mpa	4.4/2.6
Refrigerant Pipe Connections (inch)	Gas	5/8"
	Liquid	3/8"
Drain Pipe (OD)	mm	25
Ambient Temperature Cooling	°C	20°C to 43°C
	°F	68°F to 109.4°F
Ambient Temperature Heating	°C	-5°C to 16°C
	°F	23°F to 60.8°F
Ambient Temperature	°C	16°C to 20°C
Fan only	°F	60.8°F to 68°F



Notes:

1. Outdoor air temperature 33°C DB, 28°C WB; equivalent refrigerant piping length 8m with zero level difference.
2. Outdoor air temperature 0°C DB, -2.9°C WB; equivalent refrigerant piping length 8m with zero level difference.
3. Stable operation external static pressure range. (Note: setting external static pressure outside the unit's optimal static pressure range may lead to higher noise levels and lower airflow rate. For the optimal external static pressure range refer to the unit's installation manual.)
4. Sound pressure level is measured 1.4m below the unit in a semi-anechoic chamber.

OPTIONAL ACCESSORIES

Wired Thermostat CTVS-C-WR86E/KD (not included)

Note – Due to Comfort Time ongoing commitment to quality, specifications, ratings and dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service, Maintenance and operation may cause property damage on personal injury.

Installation, service and operation must be performed by a qualified installer, servicing and operation agency.

DIMENSIONAL DRAWINGS - INCHES (MM)
