

Job: _____
Location: _____
Schedule No.: _____
System Designation: _____

Engineer: _____
Architect: _____
Date: _____
For: **Reference** **Approval** **Review** **Construction**

FEATURES

- All DC Inverter Technology
- Wide Application Range
- Flexible Control and Easy Maintenance
- 7 Speed
- Single Fan Motor
- Heating and Cooling
- High-lift Drain Pump
- Two Blowers
- Convenient Installation

SPECIFICATIONS

PERFORMANCE

Nominal Cooling Capacity	Btu/h	153,600
	Kw	45
Nominal Heating Capacity	Btu/h	191,100
	Kw	56

ELECTRICAL DATA

Power Supply	V/Ph/Hz	220-240/1/50-60
Power Input (10 Pa) Cooling	Kw	1800
Power Input (10 Pa) Heating	Kw	1800
Min. Voltage	Volts	198
Max. Voltage	Volts	264
MCA	Amp	12.50
MFA	Amp	30
Rated Motor Output	Kw	1.84
FLA	Amp	12.40

GENERAL DATA

Airflow rate 3	m3/h (CFM)	6500 (3825)
	m3/h (CFM)	6150 (3619)
	m3/h (CFM)	5800 (3413)
	m3/h (CFM)	5450 (3207)
	m3/h (CFM)	5100 (3001)
	m3/h (CFM)	4750 (2795)
	m3/h (CFM)	4400 (2589)
Sound pressure level 5	dB(A)	60
	dB(A)	59
	dB(A)	58
	dB(A)	57
	dB(A)	55
	dB(A)	54
	dB(A)	52
Dimmension	Net (mm)	2010×680×905
	Packed (mm)	2095×800×964
Body Net/Gross weight	KG (Lbs)	220/245 (485.0/540.1)
Refrigerant type		R410A
Design pressure (H/L)	Mpa	4.4 / 2.6
Refrigerant Pipe Connections (inch)	Gas	5/8"
	Liquid	1-1/8"
Drain Pipe	inch	1-17/64"



Notes:

1. Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
2. Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
3. Fan motor speed and air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
4. Stable operation external static pressure range. (Note: setting external static pressure outside the unit's optimal static pressure range may lead to higher noise levels and lower airflow rate. For the optimal external static pressure range refer to the unit's installation manual.)
5. Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured 1.4m below the unit in a semi-anechoic chamber.
6. Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

OPTIONAL ACCESSORIES

Wired Thermostat CTVS-C-WR86E/KD (not included)

Note – Due to Comfort Time ongoing commitment to quality, specifications, ratings and dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service, Maintenance and operation may cause property damage or personal injury. Installation, service and operation must be performed by a qualified installer, servicing and operation agency.

DIMENSIONAL DRAWINGS - INCHES (MM)
